

2012 Sony AR Series Speakers



		
Model	SS-AR1	SS-AR2
Starting At	\$27,000 / Pair	\$20,000 / Pair
System	4-unit, 3-way, floor-standing vented box speaker system	4-unit, 3-way, floor-standing vented box speaker system
Drivers	25 mm (1 inch) soft dome 130 mm (5 inch) sliced-paper cone Twin 200 mm (8 inch) aluminum cone	25 mm (1 inch) soft dome 130 mm (5 inch) sliced-paper cone Twin 165 mm (6 1/2 inch) aluminum cone
Frequency Response	28 Hz to 60 kHz	42 Hz to 60 kHz
Crossover Response	400 Hz, 4 kHz multi-slope network	400 Hz, 4 kHz multi-slope network
Sensitivity	88 dB (2.83 V/m)	89 dB (2.83 V/m)
Nominal Impedance	4 ohms	4 ohms
Maximum Input Power	200 W	100 W
Dimensions (WxHxD) Excluding Protruding Parts	12 5/8 x 41 1/2 x 17 3/4 inches (320 x 1055 x 450 mm)	11 1/8 x 37 5/8 x 14 7/8 inches (280 x 955 x 375 mm)
Dimensions (WxHxD) Including Protruding Parts	12 5/8 x 42 5/8 x 19 3/8 inches (320 x 1080 x 490 mm)	11 1/8 x 38 5/8 x 16 1/4 inches (280 x 980 x 410 mm)
Weight	126 lbs (57 kg)	84 lbs (38 kg)
Supplied Accessories	Speaker grills (2) Cleaning cloth	Speaker grills (2) Cleaning cloth