

## STR-ZA1000ES

### ES 7.2CH 4K AV RECEIVER

The perfect center to your automated home entertainment universe now with just the right amount of: flexible, multi-zone High Definition connectivity, easy IP integration with leading control systems, powerful browser-based configurability, and well-renowned ES build quality for an incredible Audio/Video experience that you won't easily forget.



### Bullets

---

- 7.2 Ch. A/V Receiver (90W + 90W @ 6 Ohms, 20 – 20kHz, 0.09% THD)
- Optimized chassis and internal circuitry for incredible audio performance
- HDMI® with HDCP 2.2 support (5-in, 2-out: 1-main, 1-2nd zone)<sup>1</sup>
- Flexible HD connectivity with 7 assignable inputs (5 HDMI®, 2 component)<sup>1</sup>
- Optimized for custom in-home integration/system configuration
- Convenient front USB for system setup and updating<sup>2</sup>
- Web browser configurable set-up (programming)
- Seamless IP Control integration (1-port) with the leading control systems<sup>3</sup>
- Supports 4K upscaling<sup>4</sup> and pass-through with 3D and full TRILUMINOS™ color support<sup>5</sup>
- In-ceiling mode for natural, rich front-channel sound staging
- Flexible, full-resolution multi-zone distribution capability<sup>3</sup>
- Installer friendly remote commander with preset discrete command codes
- 1, 12-Volt triggers for triggering external peripherals, amplifiers, etc.<sup>3</sup>
- 3, IR repeaters (1-in, 2-out) for external device control<sup>3</sup>
- Supports Digital Cinema Surround, Dolby®, and dts® Digital Surround Audio Codecs
- Advanced Digital Cinema Audio Calibration for quick Set-Up
- Sony® ES 5-Year Limited Warranty<sup>6</sup>

### Features

---

#### Beautiful seven-channel sound

With 90W per channel, the STR-ZA1000 delivers cinema-like surround sound and crystal clear music reproduction (90W + 90W @ 6 Ohms, 20 – 20kHz, 0.09% THD). For special installations, the amplifier can be configured to support: 2 pairs of speakers either independently (A or B) or simultaneously (A and B), in addition to Bi-Amp fashion.

#### Built for sound

Every detail from the removable aluminum faceplate, to electronic component selection, special 2nd generation ES solder, structural/chassis elements, and even screw placement has been scrutinized and tuned in the higher interest of reliably consistent sound performance.

#### 7 High Definition inputs for system flexibility

Flexible HD connectivity with 7 assignable inputs (5 HDMI®, 2 component). HDCP 2.2 compliant this ES receiver also supports simple connectivity and full-playback of "4K Premium Content" with maximum visual and multi-channel sound quality.<sup>1</sup> In addition the ZA1000ES allows full, native 4K video content pass-through to 4K capable televisions and projectors, and even up-scales high definition movies and TV shows to 4K quality.<sup>5</sup>

## **Optimized for custom in-home integration**

Designed with the integrator in mind, Sony ES engineers took the class leading AVR GUI and tailored it for fluid integration into leading control systems using the front panel display or even web browser functionality. We've also redesigned the back panel layout to make wiring in a rack easier. Whether it's including an Install manual with a product manual or discrete IR codes in the remote, we've focused on helping you exceed your customers' expectations.

## **USB Front Input**

Using the front mounted USB, you can easily apply system updates and during setup, save all receiver settings to a flash drive for backing up and porting over to another unit to replicate settings.<sup>2</sup>

## **Web Browser configurable**

View, program and edit receiver settings via your Web Browser, computer, smartphone, or tablet. Enter the following into your web browser: "http://[receiver's ip-address]". \* — Most modern web browsers are supported.

## **Seamless IP integration**

The perfect partner for home automation. With help from an authorized ES dealer/installer the full power of an ES receiver can be easily integrated into expanded home automation including multi-zone audio, lighting and shades, security, appliances and almost anything else you can imagine. With built-in support for: Control4® with SDDP, Crestron, AMX Beacon, Savant, URC, RTI, Elan, Vantage, Gefen and AMX Beacon, the STR-ZA2000ES also features (1) 12-volt trigger, RS232 and IR, for added installation flexibility.<sup>3</sup>

## **'PING' button**

Easing the IP integration process is the addition of a 'PING' button on the front of the unit for quick access to unit-specific IP information (IP and MAC address) via the front display and also easy sharing of unit 'discovery' protocols with 3rd party CI controllers.

## **In-Ceiling speaker mode**

Developed especially for use with in-ceiling speakers and easily configured during setup, In-Ceiling Speaker Mode virtually relocates the Front and Center in-ceiling speaker sound images to better coincide with the screen. Dialog and music will sound as if coming from the screen instead of the ceiling.

## **Flexible zone distribution**

Flexible zone distribution capability allows a Z-Series receiver to distribute audio/video sources to the 1st and 2nd zones in varying configurations providing expanded options.

## **Discretion advised...**

Enjoy enhanced system integration, with The supplied remote control, Call up Test Tones and Video signals at the push of a button. Access frequently used Menu settings, or take advantage of discrete IR codes to ensure that remote commands perform as advertised.

## **Full HDMI® color gamut support**

With x.v.Color™ and Deep Color technology capability, you can rest assured that all HDMI® connected video sources will look their best, displaying nearly twice (1.8x) as many viewable colors as the existing RGB color standard.<sup>1</sup>

## **Only what's necessary...**

A powerful catalog of playback CODECs: Digital Cinema Surround, Dolby®, dts® Digital Surround, and Neo:6 Cinema Audio Codec support ensure an optimized listening experience every time.

## **Advanced Digital Cinema Auto Calibration — Quick Speaker Set Up**

A powerful integration tool, Advanced Digital Cinema Auto Calibration with Auto Phase Matching (APM) functionality ensures automatic, optimized audio output settings based on speaker distance and placement (microphone supplied).

## **Sony® ES 5-Year Limited Warranty**

All ES-Series receivers come with an industry leading 5-year parts and labor warranty, 90-day advanced exchange program, and dedicated toll-free support line staffed by CEDIA-trained product experts. (1-877-619-7669; Monday – Friday 10am – 7pm ET)<sup>6</sup>

## Amplifier/Receiver

### AMPLIFIER FEATURES

Bi-AMP	Yes
Digital Legato Linear	Yes
Number of Amp channels	7 channels
Sound Optimizer	Yes
Speaker Impedance	6 – 16 Ohms
Speaker Selector	A/B, A+B, Off
Speaker Terminal	Screw (Ni)
Sub Woofer X' Over	17 points (40 – 200Hz)

### AMPLIFIER POWER

6 Ohms, 20 – 20kHz, 2ch driven	90W + 90W, THD .09%
--------------------------------	---------------------

### CIS & CONTROL FEATURES

2nd A	Speaker & Line (Variable & Fixed)
-------	-----------------------------------

### DCAC FEATURES

Automatic Phase Matching	Yes
DCAC	Advanced D.C.A.C
Mic	Mono

### NETWORK FEATURES

CIS IP Control	Yes
----------------	-----

## Audio Features

### DECODING FORMAT

192kHz / 24bit	LPCM, Yes
96kHz / 24bit	LPCM, Yes
DTS / DTS-ES (Matrix6.1 / Discrete6.1)	Yes / Yes
DTS 96 / 24	Yes
DTS HD MA/ DTS HD HR	Yes / Yes
Dolby Digital EX / Dolby Digital	Yes / Yes
Dolby Prologic / II / IIx / IIz	Yes / Yes / Yes / No
Dolby TruHD / Dolby Digital +	Yes / Yes

### SOUND FIELD

2ch	Yes
A.F.D. Auto	Yes
Analog Direct	Yes
HD-D.C.S.	Yes
Multi Stereo	Yes
Neo:6 Cinema	Yes
PLII Movie	Yes
PLIIx Movie	Yes

### TUNER

Auto Tuning	Yes
Direct Tuning	Yes
Preset Channel (FM/AM)	60 Total (30 FM, 30 AM)
Station Name	Yes

## General

### INSTALLATION

12V Trigger	1
2nd V	HDMI / Component / Composite
3rd A	Line (Variable / Fixed)
Certification (AMX / Crestron / Control 4)	Yes / Yes / Yes
IR Repeat (In / Out)	Yes (1 in / 2 out)
RS-232C for Control	Yes

### OTHER

Assignable Component Video In	Yes
Assignable HDMI Video In	Yes
Auto Standby	Yes
Detachable AC	Yes
Digital Input Assign	Yes, Optical and Coaxial
Easy Automation	Yes with Custom Preset
GUI	Yes with Easy Setup Wizard
GUI Blending Output (from Composite / Component / HDMI) (2)	Yes
GUI Language	English, French, Spanish
Pin Jack	Nickel
Power Consumption	290 W
Power Requirement	120 V, 60 Hz
Sleep Timer	Yes (up to 2 hours)
Update Capability	Yes, via USB

## Inputs and Outputs

### AUDIO INPUTS

Analog Audio In	4
Coaxial	1
Optical In	2

### OTHER INPUTS AND OUTPUTS

USB	1 (front, for setting Save / Load)
-----	------------------------------------

### SPEAKER OUTPUTS

Center (Bass / Treble)	Yes
Center Speaker Lift Up	Yes
Front (Bass / Treble)	Yes
Front High (Bass / Treble)	Yes
Surround (Bass / Treble)	Yes
Surround Back (Bass / Treble)	Yes

### VIDEO INPUTS

Component Video In	2 (assignable)
HDMI In	5 (1 with HDCP 2.2 support) (1 front)

### VIDEO OUTPUTS

Component Video Out	1
Composite Video Out: Inc. Monitor Out	2

HDMI Out 1 (with HDCP 2.2 support)

## Video Features

### A/V SYNC FEATURES

A/V SYNC Yes (Variable)

A/V Sync Sampling Frequency 192 kHz

A/V Sync Time (msec) 0 – 300 msec

### HDMI

3D over HDMI Yes

Audio Return Channel Yes

BRAVIA® SYNC™ (CEC Control) Yes (One Touch Play, System Audio Control, System Power Off)

DSD Yes (HDMI)

HDMI™ video output capability 4K, 1080p, 1080/24p Deep Color (up to 36 bit), TRILUMINOS™ Color (xvYCC)

Power Off Pass Through Yes

S-Select Yes

Video Up Converter (Analog Component / HDMI) Yes (Analog to HDMI)

Video Up Scaler (Analog; Component / HDMI) Yes (4K)

## Weight and Measurements

### WEIGHT AND MEASUREMENTS

Receiver Dimension (W x H x D inches) 16.9 x 6.9 x 16.1 inches

Receiver Weight (pound) 27.1 pounds

### IN THE BOX

Calibration Microphone (1)

FM Antenna (1)

AM Antenna (1)

AC Power Cord (1)

Remote Commander (1)

RO3 (size-AAA) batteries (1 pair)

Front Cover (1)

1. Requires HDMI® cable sold separately.

2. Not all USB devices are compatible.

3. May require additional accessories. Check with your authorized dealer for details.

4. 4K upscaling requires a 4K projector or 4K TV.

5. Requires capable HDTV, capable video source, and HDMI® cable sold sep.

6. For full terms and conditions please visit [www.esupport.sony.com](http://www.esupport.sony.com).

© 2014 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, 24p True Cinema and Digital Cinema Sound are trademarks of Sony Corporation. Blu-ray Disc and Blu-ray 3D are trademarks of Blu-ray Disc Association. Dolby is a registered trademark of Dolby Laboratories. dts is a trademark of dts Inc. HDMI is a trademark of HDMI Licensing LLC. All other trademarks are trademarks of their respective owners. Features and specifications are subject to change without notice.

## STR-ZA2000ES

### ES 7.2ch 4K AV Receiver

The perfect center to your automated home entertainment universe now with just the right amount of: flexible, multi-zone High Definition connectivity, easy IP integration with leading control systems, powerful browser-based configurability, and well-renowned ES build quality for an incredible Audio/Video experience that you won't easily forget.



### Bullets

- 7.2 Ch. A/V Receiver (95W + 95W @ 6 Ohms, 20 – 20kHz, 0.09% THD)
- Optimized chassis and internal circuitry for incredible audio performance
- HDMI® with HDCP 2.2 support (6-in, 2-out: 1-main, 1-2nd zone)<sup>1</sup>
- Flexible HD connectivity with 8 assignable inputs (6 HDMI®, 2 component)<sup>1</sup>
- Optimized for custom in-home integration/system configuration
- Convenient front USB for system setup and updating<sup>2</sup>
- Web browser configurable set-up (programming)
- Seamless IP Control integration (1-port) with the leading control systems<sup>3</sup>
- Supports 4K upscaling<sup>4</sup> and pass-through with 3D and full TRILUMINOS™ color support<sup>5</sup>
- In-ceiling mode for natural, rich front-channel sound staging
- Flexible, full-resolution multi-zone distribution capability<sup>3</sup>
- Installer friendly remote commander with preset discrete command codes
- 1, 12-Volt triggers for triggering external peripherals, amplifiers, etc.<sup>3</sup>
- 3, IR repeaters (1-in, 2-out) for external device control<sup>3</sup>
- Supports Digital Cinema Surround, Dolby®, and dts® Digital Surround Audio Codecs
- Advanced Digital Cinema Audio Calibration for quick Set-Up
- Sony® ES 5-Year Limited Warranty<sup>6</sup>

### Features

#### Beautiful seven-channel sound

With 95W per channel, the STR-ZA2000 delivers cinema-like surround sound and crystal clear music reproduction (95W + 95W @ 6 Ohms, 20 – 20kHz, 0.09% THD). For special installations, the amplifier can be configured to support: 2 pairs of speakers either independently (A or B) or simultaneously (A and B), in addition to Bi-Amp fashion.

#### Built for sound

Every detail from the removable aluminum faceplate, to electronic component selection, special 2nd generation ES solder, structural/chassis elements, and even screw placement has been scrutinized and tuned in the higher interest of reliably consistent sound performance.

#### 8 High Definition inputs for system flexibility

Flexible HD connectivity with 8 assignable inputs (6 HDMI®, 2 component). HDCP 2.2 compliant this ES receiver also supports simple connectivity and full-playback of "4K Premium Content" with maximum visual and multi-channel sound quality.<sup>1</sup> In addition the ZA2000ES allows full, native 4K video content pass-through to 4K capable televisions and projectors, and even up-scales high definition movies and TV shows to 4K quality.<sup>5</sup>

## **Optimized for custom in-home integration**

Designed with the integrator in mind, Sony ES engineers took the class leading AVR GUI and tailored it for fluid integration into leading control systems using the front panel display or even web browser functionality. We've also redesigned the back panel layout to make wiring in a rack easier. Whether it's including an Install manual with a product manual or discrete IR codes in the remote, we've focused on helping you exceed your customers' expectations.

## **USB Front Input**

Using the front mounted USB, you can easily apply system updates and during setup, save all receiver settings to a flash drive for backing up and porting over to another unit to replicate settings.<sup>2</sup>

## **Web Browser configurable**

View, program and edit receiver settings via your Web Browser, computer, smartphone, or tablet. Enter the following into your web browser: "http://[receiver's ip-address]/\*. \* — Most modern web browsers are supported.

## **Seamless IP integration**

The perfect partner for home automation. With help from an authorized ES dealer/installer the full power of an ES receiver can be easily integrated into expanded home automation including multi-zone audio, lighting and shades, security, appliances and almost anything else you can imagine. With built-in support for: Control4® with SDDP, Crestron, AMX Beacon, Savant, JRC, RTI, Elan, Vantage, Gefen and AMX Beacon, the STR-ZA2000ES also features (1) 12-volt trigger, RS232 and IR, for added installation flexibility.<sup>3</sup>

## **'PING' button**

Easing the IP integration process is the addition of a 'PING' button on the front of the unit for quick access to unit-specific IP information (IP and MAC address) via the front display and also easy sharing of unit 'discovery' protocols with 3rd party CI controllers.

## **In-Ceiling speaker mode**

Developed especially for use with in-ceiling speakers and easily configured during setup, In-Ceiling Speaker Mode virtually relocates the Front and Center in-ceiling speaker sound images to better coincide with the screen. Dialog and music will sound as if coming from the screen instead of the ceiling.

## **Flexible zone distribution**

Flexible zone distribution capability allows a Z-Series receiver to distribute audio/video sources to the 1st and 2nd zones in varying configurations providing expanded options.

## **Discretion advised...**

Enjoy enhanced system integration, with The supplied remote control, Call up Test Tones and Video signals at the push of a button. Access frequently used Menu settings, or take advantage of discrete IR codes to ensure that remote commands perform as advertised.

## **Full HDMI® color gamut support**

With x.v.Color™ and Deep Color technology capability, you can rest assured that all HDMI® connected video sources will look their best, displaying nearly twice (1.8x) as many viewable colors as the existing RGB color standard.<sup>1</sup>

## **Only what's necessary...**

A powerful catalog of playback CODECs: Digital Cinema Surround, Dolby®, dts® Digital Surround, and Neo:6 Cinema Audio Codec support ensure an optimized listening experience every time.

## **Advanced Digital Cinema Auto Calibration — Quick Speaker Set Up**

A powerful integration tool, Advanced Digital Cinema Auto Calibration with Auto Phase Matching (APM) functionality ensures automatic, optimized audio output settings based on speaker distance and placement (microphone supplied).

## **Sony® ES 5-Year Limited Warranty**

All ES-Series receivers come with an industry leading 5-year parts and labor warranty, 90-day advanced exchange program, and dedicated toll-free support line staffed by CEDIA-trained product experts. (1-877-619-7669; Monday – Friday 10am – 7pm ET)<sup>6</sup>

## Amplifier/Receiver

### AMPLIFIER FEATURES

Bi-AMP	Yes
Digital Legato Linear	Yes
Number of Amp channels	7 channels
Sound Optimizer	Yes
Speaker Impedance	6 – 16 Ohms
Speaker Selector	A/B, A+B, Off
Speaker Terminal	Screw (Ni)
Sub Woofer X' Over	17 points (40 – 200Hz)

### AMPLIFIER POWER

6 Ohms, 20 – 20kHz, 2ch driven	95W + 95W, THD .09%
--------------------------------	---------------------

### CIS & CONTROL FEATURES

2nd A	Speaker & Line (Variable & Fixed)
-------	-----------------------------------

### DCAC FEATURES

Automatic Phase Matching	Yes
DCAC	Advanced D.C.A.C
Mic	Mono

### NETWORK FEATURES

CIS IP Control	Yes
----------------	-----

## Audio Features

### DECODING FORMAT

192kHz / 24bit	LPCM, Yes
96kHz / 24bit	LPCM, Yes
DTS / DTS-ES (Matrix6.1 / Discrete6.1)	Yes / Yes
DTS 96 / 24	Yes
DTS HD MA/ DTS HD HR	Yes / Yes
Dolby Digital EX / Dolby Digital	Yes / Yes
Dolby Prologic / II / IIx / IIz	Yes / Yes / Yes / No
Dolby TruHD / Dolby Digital +	Yes / Yes

### SOUND FIELD

2ch	Yes
A.F.D. Auto	Yes
Analog Direct	Yes
HD-D.C.S.	Yes
Multi Stereo	Yes
Neo:6 Cinema	Yes
PLII Movie	Yes
PLIIx Movie	Yes

### TUNER

Auto Tuning	Yes
Direct Tuning	Yes
Preset Channel (FM/AM)	60 Total (30 FM, 30 AM)
Station Name	Yes



## General

### INSTALLATION

12V Trigger	1
2nd V	HDMI / Component / Composite
3rd A	Line (Variable / Fixed)
Certification (AMX / Crestron / Control 4)	Yes / Yes / Yes
IR Repeat (In / Out)	Yes (1-in, 2-out)
RS-232C for Control	Yes

### OTHER

Assignable Component Video In	Yes
Assignable HDMI Video In	Yes
Auto Standby	Yes
Detachable AC	Yes
Digital Input Assign	Yes, Optical and Coaxial
Easy Automation	Yes with Custom Preset
GUI	Yes with Easy Setup Wizard
GUI Blending Output (from Composite / Component / HDMI) (2)	Yes
GUI Language	English, French, Spanish
Pin Jack	Nickel
Power Consumption	290 W
Power Requirement	120 V, 60 Hz
Sleep Timer	Yes (up to 2 hours)
Update Capability	Yes, via USB

## Inputs and Outputs

### AUDIO INPUTS

Analog Audio In	4
Coaxial	1
Optical In	2

### OTHER INPUTS AND OUTPUTS

USB	1 (front, for setting Save / Load)
-----	------------------------------------

### SPEAKER OUTPUTS

Center (Bass / Treble)	Yes
Center Speaker Lift Up	Yes
Front (Bass / Treble)	Yes
Front High (Bass / Treble)	Yes
Surround (Bass / Treble)	Yes
Surround Back (Bass / Treble)	Yes

### VIDEO INPUTS

Component Video In	2 (assignable)
HDMI In	6 (1 with HDCP 2.2 support) (1 front)

## VIDEO OUTPUTS

Component Video Out	1
Composite Video Out: Inc. Monitor Out	2
HDMI Out	1 (with HDCP 2.2 support)

## Video Features

### A/V SYNC FEATURES

A/V SYNC	Yes (Variable)
A/V Sync Sampling Frequency	192 kHz
A/V Sync Time (msec)	0 – 300 msec

### HDMI

3D over HDMI	Yes
Audio Return Channel	Yes
BRAVIA® SYNC™ (CEC Control)	Yes (One Touch Play, System Audio Control, System Power Off)
DSD	Yes (HDMI)
HDMI™ video output capability	4K, 1080p, 1080/24p Deep Color (up to 36 bit), TRILUMINOS™ Color (xvYCC)
Power Off Pass Through	Yes
S-Select	Yes
Video Up Converter (Analog Component / HDMI)	Yes (Analog to HDMI)
Video Up Scaler (Analog Component / HDMI)	Yes (4K)

## Weight and Measurements

### WEIGHT AND MEASUREMENTS

Receiver Dimension (W x H x D inches)	16.9 x 6.9 x 16.1 inches
Receiver Weight (pound)	28.7 pounds

### IN THE BOX

Calibration Microphone (1)
FM Antenna (1)
AM Antenna (1)
AC Power Cord (1)
Remote Commander (1)
R03 (size-AAA) batteries (1 pair)
Front Cover (1)

1. Requires HDMI® cable sold separately.

2. Not all USB devices are compatible.

3. May require additional accessories. Check with your authorized dealer for details.

4. 4K upscaling requires a 4K projector or 4K TV.

5. Requires capable HDTV, capable video source, and HDMI® cable sold sep.

6. For full terms and conditions please visit [www.esupport.sony.com](http://www.esupport.sony.com).

© 2014 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, 24p True Cinema and Digital Cinema Sound are trademarks of Sony Corporation. Blu-ray Disc and Blu-ray 3D are trademarks of Blu-ray Disc Association. Dolby is a registered trademark of Dolby Laboratories. dts is a trademark of dts Inc. HDMI is a trademark of HDMI Licensing LLC. All other trademarks are trademarks of their respective owners. Features and specifications are subject to change without notice.

## STR-ZA3000ES

### ES 7.2ch 4K AV Receiver

The perfect center to your automated home entertainment universe now with just the right amount of: flexible, multi-zone High Definition connectivity, easy IP integration with leading control systems, powerful browser-based configurability, and well-renowned ES build quality for an incredible Audio/Video experience that you won't easily forget.



### Bullets

---

- 7.2 Ch. A/V Receiver (100W + 100W @ 6 Ohms, 20 – 20kHz, 0.09% THD)
- Optimized chassis and internal circuitry for incredible audio performance
- HDMI® with HDCP 2.2 support (6-in, 2-out: 1-main, 1-2nd zone)<sup>1</sup>
- Flexible HD connectivity with 8 assignable inputs (6 HDMI®, 2 component)<sup>1</sup>
- 8-port Giga Ethernet Hub with PoE (2) support<sup>2</sup> for flexible connectivity
- Convenient front USB for system updating and setup<sup>3</sup>
- Web browser configurable set-up (programming)
- Optimized for custom in-home integration, and system configuration
- Seamless IP Control integration with the leading control systems<sup>4</sup>
- Supports 4K upscaling<sup>5</sup> and pass-through with 3D and full TRILUMINOS™ color support<sup>6</sup>
- In-ceiling mode for natural, rich front-channel sound staging
- Flexible, full-resolution multi-zone distribution capability<sup>4</sup>
- Installer friendly remote commander with preset discrete command codes
- 3, 12-Volt triggers for triggering external peripherals, amplifiers, etc.<sup>4</sup>
- 3, IR repeaters (1-in, 2-out) for external device control<sup>4</sup>
- Supports Digital Cinema Surround, Dolby®, and dts® Digital Surround Audio Codecs
- Advanced Digital Cinema Audio Calibration for quick Set-Up
- Sony® ES 5-Year Limited Warranty<sup>7</sup>

### Features

---

#### Beautiful seven-channel sound

With 100W per channel, the STR-ZA3000 delivers cinema-like surround sound and crystal clear music reproduction (100W + 100W @ 6 Ohms, 20 – 20kHz, 0.09% THD). For special installations, the amplifier can be configured to support: 2 pairs of speakers either independently (A or B) or simultaneously (A and B), in addition to Bi-Amp fashion.

#### Built for sound

Every detail from the removable aluminum faceplate, to electronic component selection, special 2nd generation ES solder, structural/chassis elements, and even screw placement has been scrutinized and tuned in the higher interest of reliably consistent sound performance.

#### 8 High Definition inputs for system flexibility

Flexible HD connectivity with 8 assignable inputs (6 HDMI®, 2 component). HDCP 2.2 compliant this ES receiver also supports simple connectivity and full-playback of "4K Premium Content" with maximum visual and multi-channel sound quality.<sup>1</sup> In addition the ZA3000ES allows full, native 4K video content pass-through to 4K capable televisions and projectors, and even up-scales high definition movies and TV shows to 4K quality.<sup>6</sup>

## **Optimized for custom in-home integration**

Designed with the integrator in mind, Sony ES engineers took the class leading AVR GUI and tailored it for fluid integration into leading control systems using the front panel display or even web browser functionality. We've also redesigned the back panel layout to make wiring in a rack easier. Whether it's including an Install manual with a product manual or discrete IR codes in the remote, we've focused on helping you exceed your customers' expectations.

## **8-Port Audio grade Giga Ethernet Switch**

An 8-Port Ethernet switch with PoE, Power over Ethernet functionality<sup>2</sup> (2 outlets), Ideal for local interfacing to: leading control systems, computers, media boxes, Blu-Ray Disc™ players, and game consoles directly through the receiver.

## **USB Front Input**

Using the front mounted USB, you can easily apply system updates and during setup, save all receiver settings to a flash drive for backing up and porting over to another unit to replicate settings.<sup>3</sup>

## **Web Browser configurable**

View, program and edit receiver settings via your Web Browser, computer, smartphone, or tablet. Enter the following into your web browser\*: "http://[receiver's ip-address]/". \* — Most modern web browsers are supported.

## **Seamless IP Integration**

With help from your authorized ES dealer/installer the full power of an ES receiver can easily integrated into expanded home automation including multi-zone audio, lighting and shades, security, appliances and almost anything else you can imagine. Control4® Certified and featuring Crestron Connected™, AMX Beacon, Savant, URC and RTI support, The STR-ZA3000ES also features 12-volt triggers, RS232 and IR, for added installation flexibility.<sup>4</sup>

## **'PING' button**

Easing the IP integration process is the addition of a 'PING' button on the front of the unit for quick access to unit-specific IP information (IP and MAC address) via the front display and also easy sharing of unit 'discovery' protocols with 3rd party CI controllers.

## **In-Ceiling speaker mode**

Developed especially for use with in-ceiling speakers and easily configured during setup, In-Ceiling Speaker Mode virtually relocates the Front and Center in-ceiling speaker sound images to better coincide with the screen. Dialog and music will sound as if coming from the screen instead of the ceiling.

## **Flexible zone distribution**

Flexible zone distribution capability allows a Z-Series receiver to distribute audio/video sources to the 1st and 2nd zones in varying configurations providing expanded options.

## **Discretion advised...**

Enjoy enhanced system integration, with The supplied remote control, Call up Test Tones and Video signals at the push of a button. Access frequently used Menu settings, or take advantage of discrete IR codes to ensure that remote commands perform as advertised.

## **Full HDMI® color gamut support**

With x.v.Color™ and Deep Color technology capability, you can rest assured that all HDMI® connected video sources will look their best, displaying nearly twice (1.8x) as many viewable colors as the existing RGB color standard.<sup>1</sup>

## **Only what's necessary...**

A powerful catalog of playback CODECs: Digital Cinema Surround, Dolby®, dts® Digital Surround, and Neo:6 Cinema Audio Codec support ensure an optimized listening experience every time...

## **Advanced Digital Cinema Auto Calibration — Quick Speaker Set Up**

A powerful integration tool, Advanced Digital Cinema Auto Calibration with Auto Phase Matching (APM) functionality ensures automatic, optimized audio output settings based on speaker distance and placement (microphone supplied).

## **Sony® ES 5-Year Limited Warranty**

All ES-Series receivers come with an industry leading 5-year parts and labor warranty, 90-day advanced exchange program, and dedicated toll-free support line staffed by CEDIA-trained product experts. (1-877-619-7669; Monday – Friday 10am – 7pm ET)<sup>7</sup>

## Amplifier/Receiver

### AMPLIFIER FEATURES

Bi-AMP	Yes
Digital Legato Linear	Yes
Number of Amp channels	7 channels
Sound Optimizer	Yes
Speaker Impedance	6 – 16 Ohms
Speaker Selector	A/B, A+B, Off
Speaker Terminal	Screw (Ni)
Sub Woofer X' Over	17 points (40 – 200Hz)

### AMPLIFIER POWER

6 Ohms, 20 – 20kHz, 2ch driven	100W + 100W, THD .09%
--------------------------------	-----------------------

### CIS & CONTROL FEATURES

2nd A	Speaker & Line (Variable & Fixed)
-------	-----------------------------------

### DCAC FEATURES

Automatic Phase Matching	Yes
DCAC	Advanced D.C.A.C
Mic	Mono

### NETWORK FEATURES

CIS IP Control	Yes
Network Update	No

## Audio Features

### DECODING FORMAT

192kHz / 24bit	LPCM, Yes
96kHz / 24bit	LPCM, Yes
DTS / DTS-ES (Matrix6.1 / Discrete6.1)	Yes / Yes
DTS 96 / 24	Yes
DTS HD MA / DTS HD HR	Yes / Yes
Dolby Digital EX / Dolby Digital	Yes / Yes
Dolby Prologic / II / IIx / IIz	Yes / Yes / Yes / No
Dolby TruHD / Dolby Digital +	Yes / Yes

### SOUND FIELD

2ch	Yes
A.F.D. Auto	Yes
Analog Direct	Yes
HD-D.C.S.	Yes
Multi Stereo	Yes
Neo:6 Cinema	Yes
PLII Movie	Yes
PLIIx Movie	Yes

## TUNER

Auto Tuning	Yes
Direct Tuning	Yes
Preset Channel (FM/AM)	60 Total (30 FM, 30 AM)
Station Name	Yes

## General

### INSTALLATION

12V Trigger	3
2nd V	HDMI / Component / Composite
3rd A	Line (Variable / Fixed)
Certification (AMX/Crestron/Control 4)	Yes / Yes / Yes
IR Repeat (In/Out)	Yes (1-in, 2-out)
RS-232C for Control	Yes

### OTHER

Assignable Component Video In	Yes
Assignable HDMI Video In	Yes
Auto Standby	Yes
Detachable AC	Yes
Digital Input Assign	Yes, Optical and Coaxial
Easy Automation	Yes with Custom Preset
GUI	Yes with Easy Setup Wizard
GUI Blending Output (from Composite / Component / HDMI) (2)	Yes
GUI Language	English, French, Spanish
Pin Jack	Nickel
Power Consumption	290 W
Power Requirement	120 V, 60 Hz
Sleep Timer	Yes (up to 2 hours)
Update Capability	Yes, via USB

## Inputs and Outputs

### AUDIO INPUTS

Analog Audio In	4
Coaxial	1
Optical In	2

### AUDIO OUTPUTS

Pre Out (Center)	Yes
Pre Out (Front (L/R))	Yes
Pre Out (Subwoofer)	Yes
Pre Out (Surround (L/R))	Yes
Pre Out (Surround Back (L/R))	Yes

### OTHER INPUTS AND OUTPUTS

Ethernet (Switching HUB)	8-port Giga Ethernet Hub (with PoE support (2))
USB	1 (front, for setting Save / Load)

## SPEAKER OUTPUTS

Center (Bass/Treble)	Yes
Center Speaker Lift Up	Yes
Front (Bass/Treble)	Yes
Front High (Bass/Treble)	Yes
Surround (Bass/Treble)	Yes
Surround Back (Bass/Treble)	Yes

## VIDEO INPUTS

Component Video In	2 (assignable)
HDMI In	6 (1 front) (2 with HDCP 2.2 support)

## VIDEO OUTPUTS

Component Video Out	1
Composite Video Out	Inc. Monitor Out: 2
HDMI Out	2 (with HDCP 2.2 support)

## Video Features

### A/V SYNC FEATURES

A/V SYNC	Yes (Variable)
A/V Sync Sampling Frequency	192 kHz
A/V Sync Time (msec)	0 – 300 msec

### HDMI

3D over HDMI	Yes
Audio Return Channel	Yes
BRAVIA® SYNC™ (CEC Control)	Yes (One Touch Play, System Audio Control, System Power Off)
DSD	Yes (HDMI)
HDMI™ video output capability	4K, 1080p, 1080/24p Deep Color (up to 36 bit), TRILUMINOS™ Color (xvYCC)
Power Off Pass Through	Yes
S-Select	Yes
Video Up Converter (Analog Component / HDMI)	Yes (Analog to HDMI)
Video Up Scaler (Analog; Component /HDMI)	Yes (4K)

## Weight and Measurements

### WEIGHT AND MEASUREMENTS

Receiver Dimension (W x H x D inches)	16.9 x 6.9 x 16.1 inches
---------------------------------------	--------------------------

### WEIGHT AND MEASUREMENTS (CONT'D)

Receiver Weight (pound)	29.5 pounds
-------------------------	-------------

### IN THE BOX

Calibration Microphone (1)
FM Antenna (1)
AM Antenna (1)
AC Power Cord (1)
Remote Commander (1)
R03 (size-AAA) batteries (1 pair)
Front Cover (1)



1. Requires HDMI® cable sold separately.
2. Not all USB devices are compatible.
3. May require additional accessories. Check with your authorized dealer for details.
4. 4K upscaling requires a 4K projector or 4K TV.
5. Requires capable HDTV, capable video source, and HDMI® cable sold sep.
6. For full terms and conditions please visit [www.esupport.sony.com](http://www.esupport.sony.com).

© 2014 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, 24p True Cinema and Digital Cinema Sound are trademarks of Sony Corporation. Blu-ray Disc and Blu-ray 3D are trademarks of Blu-ray Disc Association. Dolby is a registered trademark of Dolby Laboratories. dts is a trademark of dts Inc. HDMI is a trademark of HDMI Licensing LLC. All other trademarks are trademarks of their respective owners. Features and specifications are subject to change without notice.



## STR-ZA5000ES

### 9.2 Channel 4K AV Receiver

The perfect center to your automated home entertainment universe now with just the right amount of: flexible, multi-zone, high-definition connectivity, easy IP integration with leading control systems, powerful browser-based configurability, and well-renowned ES build quality for an incredible Audio/Video experience that you won't easily forget.



### Bullets

---

- 9.2 Ch. A/V Receiver (130W @ 8 ohms, 1 kHz, THD 0.9%)
- Supports Dolby ATMOS and DTS:X decoding up to 11.1ch (using 2 extra power amplifiers).
- Optimized chassis and internal circuitry for incredible audio performance
- HDMI® with HDCP 2.2 support (6in/2out)<sup>1</sup>
- Flexible HD connectivity with 8 assignable inputs (6 HDMI, 2 component)<sup>1</sup>
- 8-port Giga Ethernet Hub with PoE (x2) support<sup>2</sup> for flexible connectivity
- Convenient front USB for system updating and setup<sup>3</sup>
- Web browser configurable set-up (programming)
- Optimized especially for custom in-home integration, and system configuration
- Seamless IP Control integration with the leading control systems<sup>4</sup>
- Supports 4K upscaling<sup>5</sup> and pass-through with 3D and full TRILUMINOS™ color support<sup>6</sup>
- In-ceiling mode for natural, rich front-channel sound staging
- Flexible, full-resolution multi-zone distribution capability<sup>4</sup>
- Installer friendly remote commander with preset discrete command codes
- 3, 12-Volt triggers for triggering external peripherals, amplifiers, etc.<sup>4</sup>
- 3, IR repeaters (1-in, 2-out) for external device control<sup>4</sup>
- Advanced Digital Cinema Audio Calibration for quick Set-Up
- Sony® ES 5-Year Limited Warranty<sup>7</sup>

### Features

---

#### Beautiful nine-channel object based surround sound

With 130W per channel, the STR-ZA5000ES delivers cinema-like surround sound and crystal clear music reproduction (130W @ 8 ohms, 1 kHz, THD 0.9%). For special installations, the amplifier can be configured to support: 2 pairs of speakers either independently (A or B) or simultaneously (A and B), in addition to Bi-Amp fashion.

#### Supports Dolby Atmos®, and DTS:X® object based surround

You'll feel like you're inside the action as the sounds of people, music, and things move all around you in three-dimensional space.

#### Built for sound

Every detail from the removable aluminum faceplate, to electronic component selection, special 2nd generation ES solder, structural/chassis elements, and even screw placement has been scrutinized and tuned in the higher interest of reliably consistent sound performance. The STR-ZA5000ES offers improved structural stability for better sound via the analogue signal path. This circuit is located on a glass epoxy board, in order to achieve higher speed and power. The STR-ZA5000ES also features high-quality speaker terminals with gold plating.

## **8 High Definition inputs for system flexibility<sup>14</sup>**

Flexible HD connectivity with 8 assignable inputs (6 HDMI®, 2 component). HDCP 2.2 compliant this ES receiver also supports simple connectivity and full-playback of "4K Premium Content" with maximum visual and multi-channel sound quality.<sup>1</sup> In addition the ZA5000ES allows full, native 4K video content pass-through to 4K capable televisions and projectors, and even up-scales high definition movies and TV shows to 4K quality.<sup>6</sup>

## **Optimized for custom in-home integration**

Designed with the integrator in mind, Sony ES engineers took the class leading AVR GUI and tailored it for fluid integration into leading control systems using the front panel display or even web browser functionality. We've also redesigned the back panel layout to make wiring in a rack easier. Whether it's including an Install manual with a product manual or discrete IR codes in the remote, we've focused on helping you exceed your customers' expectations.

## **8-Port Audio grade Giga Ethernet Switch**

An 8-Port Ethernet switch with PoE, Power over Ethernet functionality<sup>2</sup> (2 outlets), Ideal for local interfacing to: leading control systems, computers, media boxes, Blu-Ray Disc™ players, and game consoles directly through the receiver.

## **USB Front Input**

Using the front mounted USB, you can easily apply system updates and during setup, save all receiver settings to a flash drive for backing up and porting over to another unit to replicate settings.<sup>3</sup>

## **Web Browser configurable**

View, program and edit receiver settings via your Web Browser, computer, smartphone, or tablet. Enter the following into your web browser\*: "http://[receiver's ip-address]/". \* — Most modern web browsers are supported.

## **Seamless IP Integration**

With help from your authorized ES dealer/installer the full power of an ES receiver can be easily integrated into expanded home automation including multi-zone audio, lighting and shades, security, appliances and almost anything else you can imagine. Control4® Certified and featuring Crestron Connected™, AMX Beacon, Savant, URC and RTI support, The STR-ZA5000ES also features 12-volt triggers, RS232 and IR, for added installation flexibility.<sup>4</sup>

## **'PING' button**

Easing the IP integration process is the addition of a 'PING' button on the front of the unit for quick access to unit-specific IP information (IP and MAC address) via the front display and also easy sharing of unit 'discovery' protocols with 3rd party CI controllers.

## **In-Ceiling speaker mode**

Developed especially for use with in-ceiling speakers and easily configured during setup, In-Ceiling Speaker Mode virtually relocates the Front and Center in-ceiling speaker sound images to better coincide with the screen. Dialog and music will sound as if coming from the screen instead of the ceiling.

## **Flexible zone distribution**

Flexible zone distribution capability allows a Z-Series receiver to distribute audio/video sources to the 1st and 2nd zones in varying configurations providing expanded options.

## **Discretion advised...**

Enjoy enhanced system integration, with The supplied remote control, Call up Test Tones and Video signals at the push of a button. Access frequently used Menu settings, or take advantage of discrete IR codes to ensure that remote commands perform as advertised.

## **Full HDMI® color gamut support**

With x.v.Color™ and Deep Color technology capability, you can rest assured that all HDMI® connected video sources will look their best, displaying nearly twice (1.8x) as many viewable colors as the existing RGB color standard.<sup>1</sup>

## **Only what's necessary...**

A powerful catalog of playback CODECs: Digital Cinema Surround, Dolby®, dts® Digital Surround, and Neo:6 Cinema Audio Codec support ensure an optimized listening experience every time...

## Advanced Digital Cinema Auto Calibration – Quick Speaker Set Up

A powerful integration tool, Advanced Digital Cinema Auto Calibration with Auto Phase Matching (APM) functionality ensures automatic, optimized audio output settings based on speaker distance and placement (microphone supplied).

## Sony® ES 5-Year Limited Warranty

All ES-Series receivers come with an industry leading 5-year parts and labor warranty, 90-day advanced exchange program, and dedicated toll-free support line staffed by CEDIA-trained product experts. (1-877-619-7669; Monday – Friday 10am – 7pm ET)<sup>7</sup>

### Amplifier/Receiver

#### AMPLIFIER FEATURES

Number of Amp channels	9 channels
Decodable Channel number	11.1 channels
Sound Optimizer	Yes
Speaker Impedance	4-16 Ohms
Speaker Selector	A/B, A+B, Off
Speaker Terminal	Screw (Gold Plated)
Bi-AMP	Yes
Digital Legato Linear	Yes

#### AMPLIFIER POWER

8 Ohms, 1kHz, 2ch driven	130W + 130W, THD .09%
--------------------------	-----------------------

#### DCAC FEATURES

Automatic Phase Matching	Yes
DCAC	Advanced D.C.A.C EX
Mic	Stereo

#### NETWORK FILTERS

Update NETWORK/USB	Yes / Yes
--------------------	-----------

#### HDMI

IN / OUT	6 / 2
HDCP 2.2 Repeater	6 / 2 (4K 60p 4:4:4)

#### VIDEO

INPUTS COMPOSITE / COMPONENT	2 / 2(Assignable)
OUTPUTS COMPOSITE / COMPONENT	2 / -

#### AUDIO

INPUTS ANALOG/OPTICAL/COAXIAL	4 / 2 / 1
AUDIO PRE-OUTS	11.2 channels

### Audio Features

#### DECODING FORMAT

192kHz / 24bit	LPCM, Yes
96kHz / 24bit	LPCM, Yes
DTS:X	Yes

DTS / DTS-ES (Matrix6.1 / Discrete6.1)	Yes / Yes
DTS 96 / 24	Yes
DTS HD MA / DTS HD HR	Yes / Yes
Dolby Atmos	Yes
Dolby Digital EX / Dolby Digital	Yes / Yes
Dolby Prologic / II / IIx / IIz	Yes / Yes / Yes / -
Dolby TruHD / Dolby Digital +	Yes / Yes
<b>SOUND FIELD</b>	
2ch Stereo	Yes
DIRECT	Yes
A.F.D.	Yes
Dolby Surround	Yes
Neural:X	Yes
Multi Stereo	Yes
PLII Movie	Yes
PLIIx Movie	Yes
<b>TUNER</b>	
Auto Tuning	Yes
Direct Tuning	Yes
Preset Channel (FM/AM)	60 Total (30 FM, 30 AM)
Station Name	Yes
<b>General</b>	
<b>INSTALLATION</b>	
12V Trigger	3
2nd V	HDMI / Component / Composite
3rd A	Line (Variable / Fixed)
Certification (AMX/Crestron/Control 4)	Yes / Yes / Yes
IR Repeat (In/Out)	Yes (1-in, 2-out)
RS-232C for Control	Yes
<b>OTHER</b>	
Assignable Component Video In	Yes
Assignable HDMI Video In	Yes
Auto Standby	Yes
Detachable AC	Yes
Digital Input Assign	Yes, Optical and Coaxial
Easy Automation	Yes with Custom Preset
GUI	Yes with Easy Setup Wizard
GUI Blending Output (from Composite / Component / HDMI) (2)	Yes
GUI Language	English, French, Spanish
Pin Jack	Nickel
Power Consumption	290 W
Power Requirement	120 V, 60 Hz

Sleep Timer	Yes (up to 2 hours)
Update Capability	Yes, via USB
<b>Inputs and Outputs</b>	
<b>AUDIO INPUTS</b>	
Analog Audio In	4
Coaxial	1
Optical In	2
<b>AUDIO OUTPUTS</b>	
Pre Out (Center)	Yes
Pre Out (Front (L/R))	Yes
Pre Out (Subwoofer)	Yes
Pre Out (Surround (L/R))	Yes
Pre Out (Surround Back (L/R))	Yes
<b>OTHER INPUTS AND OUTPUTS</b>	
Ethernet (Switching HUB)	8-port Giga Ethernet Hub (with PoE support (2))
USB	1 (front, for setting Save / Load)
<b>SPEAKER OUTPUTS</b>	
Center (Bass/Treble)	Yes
Center Speaker Lift Up	Yes
Front (Bass/Treble)	Yes
Front High (Bass/Treble)	Yes
Surround (Bass/Treble)	Yes
Surround Back (Bass/Treble)	Yes
<b>VIDEO INPUTS</b>	
Component Video In	2 (assignable)
HDMI In	6 (1 front) (2 with HDCP 2.2 support)
<b>VIDEO OUTPUTS</b>	
Component Video Out	1
Composite Video Out	Inc. Monitor Out: 2
HDMI Out	2 (with HDCP 2.2 support)
<b>Video Features</b>	
<b>A/V SYNC FEATURES</b>	
A/V SYNC	Yes (Variable)
A/V Sync Sampling Frequency	192 kHz
A/V Sync Time (msec)	0 – 300 msec
<b>HDMI</b>	
3D over HDMI	Yes
Audio Return Channel	Yes
BRAVIA® SYNC™ (CEC Control)	Yes (One Touch Play, System Audio Control, System Power Off)
DSD	Yes (HDMI)
HDMI™ video output capability	4K, 1080p, 1080/24p Deep Color (up to 36 bit), TRILUMINOS™ Color (xvYCC)
Power Off Pass Through	Yes
S-Select	Yes

Video Up Converter (Analog Component / HDMI)	Yes (Analog to HDMI)
--	----------------------

Video Up Scaler (Analog; Component /HDMI)	Yes (4K)
---	----------

## Weight and Measurements

### WEIGHT AND MEASUREMENTS

Receiver Dimension (W x H x D inches)	16.9 x 6.9 x 16.1 inches
---------------------------------------	--------------------------

### WEIGHT AND MEASUREMENTS (CONT'D)

Receiver Weight (pound)	29.5 pounds
-------------------------	-------------

### IN THE BOX

Calibration Microphone (1)

FM Antenna (1)

AM Antenna (1)

AC Power Cord (1)

Remote Commander (1)

R03 (size-AAA) batteries (1 pair)

Front Cover (1)

1. Requires HDMI® cable sold separately.

2. This receiver supports PoE Class 3.

3. Not all USB devices are compatible.

4. May require additional accessories. Check with your authorized dealer for details.

5. 4k upscaling requires a 4K projector or 4K TV.

6. Requires capable HDTV, capable video source, and HDMI® cable sold sep.

7. For full terms and conditions please visit [www.esupport.sony.com](http://www.esupport.sony.com).

© 2014 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony, 24p True Cinema and Digital Cinema Sound are trademarks of Sony Corporation. Blu-ray Disc and Blu-ray 3D are trademarks of Blu-ray Disc Association. Dolby is a registered trademark of Dolby Laboratories. dts is a trademark of dts Inc. HDMI is a trademark of HDMI Licensing LLC. All other trademarks are trademarks of their respective owners. Features and specifications are subject to change without notice.zm